



The C-Frame Downspray is a 360° spray jet that distributes water evenly across the wetted surface area. Stake assembly options provide savings in labour and installation time.

Features

- 45° downspray reduces the effect of wind.
- Gentle spray minimises damage to delicate plant foliage.
- Galvanised wire stake assembly incorporates shut-off clip to stop flow.
- Asta® Stake assembly incorporates a hole punch for easy installation.
- Three colour coded frames to identify flow rates.
- Quick insertion thread with leak-proof design.
- UV stabilised for long life.

Applications

Nurseries, tree lots, pot plants, home and landscaped gardens.



CFd® Downspray Black CFd® Downspray Brown CFd® Downspray Blue



CFd® Downspray Wire Stake Assembly Asta® Stake CFd® Downspray Assembly

Performance		360°	
COLOUR AND ORIFICE SIZE	PRESSURE (kPa)	FLOW (lph)	DIAMETER (m)
Black 0.8 mm	50	16	0.6
	100	22	0.6
	150	27	0.5
Brown 0.9 mm	50	20	0.6
	100	29	0.5
	150	35	0.5
Blue 1.0 mm	50	24	0.6
	100	34	0.5
	150	41	0.5

CFd® Downspray

COLOUR	ORIFICE SIZE	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
Black	0.8 mm	19005	100	90	14.4
Brown	0.9 mm	19025	100	90	14.4
Blue	1.0 mm	19015	100	90	14.4

CFd® Downspray Galvanised Wire Stake Assembly with Shut-Off Clip

COLOUR	TUBE LENGTH	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
Black	914 mm	43705	25	12	9.6
Brown	914 mm	43725	25	12	9.6
Blue	914 mm	43715	25	12	9.6

Asta® Stake CFd® Downspray Assembly

COLOUR	TUBE LENGTH	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
Blue	300 mm	17515	25	16	11.1
Blue	914 mm	17615	25	10	8.5

Specifications

DIMENSIONS ASSEMBLED		CFd® DOWNSPRAY	CFd® DOWNSPRAY WIRE STAKE ASSEMBLY	ASTA® STAKE CFd® DOWNSPRAY ASSEMBLY
HEIGHT		34 mm	950 mm	330 mm
WIDTH		25 mm	25 mm	30 mm
DEPTH		8 mm	15 mm	13 mm
WEIGHT (approx)		1.4 g	27.8 g	24.4 g
UV STABILISED MATERIALS	FRAME STAKE ADAPTOR OFF-TAKE TUBE BARB ADAPTOR STAKE	acetal	acetal polypropylene polyethylene acetal galvanised steel	acetal acetal PVC acetal polypropylene
BASE/CONNECTION TYPE: Inlet		QUICK THREAD WITH SEALING BARB 4 mm	BARB 4 mm	BARB 4 mm